



# Sand unit SR

Sand washing and recovery of fine

## Fields of application

- > Gravel and concrete sand industries
- > Desanding of bentonitic slurries used by slurry TBMS
- > Treatment of polluted soils

## Performance and competitiveness

- > A complete range of 6 units for capacities from 50 to 250 t/h of washed sand
- > MS performance: reduced delivery time, optimise investment
- > Turnkey solution for an optimal integration in different process



**Best technical and economical compromise**



**Optimised packing**



**Versatility**

# High-quality components and conception



**Moto-vibrator  
FRIEDRICH/ITALVIBRAS**



**Cyclone MS with  
anti-abrasion protection**



**Dewatering screen  
with grids ISENMAN**



**Pump  
METSO/WARMAN**



**Pumping tank  
with floating valve**



**Modularity of acces**



Type of units	Capacities (0-4 mm dewatered sand)	Tanks	Pumps	Cyclones	Dewaterers
MS 160x50 SR	50 t/h	2 x 1,4	HR 150	Ø 440 +	ES 6 x 19 6P
MS 260x80 SR	80 t/h	2,2 x 1,6	HR 150	Ø 560 +	ES 8 x 20 6P
MS 380x130 SR	130 t/h	2,5 x 2	WGR 150	Ø 650 +	ES 10 x 24 6P
MS 480x150 SR	150 t/h	3 x 2,2	WGR 200	Ø 750 +	ES 12 x 27 6P
MS 620x200 SR	200 t/h	3 x 2,2	WGR 200	Ø 2 x 650	ES 15 x 30 6P
MS 800x250 SR	250 t/h	3 x 2,2	WGR 200	Ø 2 x 650 +	ES 18 x 33 6P



value & sustain  
2 rue Pierre-Gilles de Gennes  
Pra de Serre 63960 Veyre-Monton - France  
tel +33 4 73 28 52 70 - fax +33 4 73 28 52 71  
info@m-s.fr - www.m-s.fr

**Prix de l'Entrepreneur  
de l'Année** > Prix Rhône-Alpes-Auvergne  
business vert > Prix national



Follow us on the web

