



Scalping Screen Range

409



The Maximus 409 has been developed for the smaller end user who require its versatility and ease of transport, without compromising on build quality and reliability.

Designed to cope with the heaviest applications, the Maximus 409 can be used in crushing circuits, demolition and construction waste management, aggregates, heavy rock and topsoil applications, as well as many others.

The Maximus 409 features a highly aggressive, heavy duty 2 bearing 2.74m x 1.22m (9' x 4') screen box, integrated hydraulically operated folding side conveyors, heavy duty feedhopper and a JCB Dieselmex 55kw Tier 4i stage 3a, 74 HP (55kW) Engine.

409 SPECIFICATION

Weight	Est 17,000 Kgs (37,500 Lbs)
Tracks	400 mm
Power Unit	JCB Dieselmex 55kw Tier 4i stage 3a 74 hp (55 kW)
Feeder Capacity	3.84 m ³
Belt Conveyor	1050 mm
Collection Conveyor	1000 mm
Tail Conveyor	1050 mm
Mid Size Conveyor	650 mm
Fines Conveyor	650 mm
Top Deck	2.743 x 1.220 (9' x 4')
Bottom Deck	2.743 x 1.220 (9' x 4')
Transport Length	10,500 mm (35'-7")
Transport Height	3,200 mm (11'-7")
Transport Width	2,610 mm (8'-8")

FEATURES AND BENEFITS

- Fold over side conveyors suitable for compact areas in waste transfer sites
- Heavy duty, high energy 2 bearing screen box
- Heavy duty Hardox hopper
- Long side conveyors – excellent stockpiling capacity
- Easily transported for hire contractors
- Engine shutdown protection
- Punch plate, finger decks, bofar decks, mesh all available

